



PROPUS Drill OILS

Propus oils are a range of high quality oils developed for pneumatic tool lubrication, compounded with additives to impart oiliness, emulsifying, anti-rust, extreme pressure, oxidation stability and tackiness characteristics. They are recommended for the air-line lubrication of a wide variety of heavy-duty, pneumatically operated equipment and will enhance the operation of percussion type rock drills

Propus oils may also be used in lighter duty equipment such as impact wrenches, rivet hammers, drills and reamers, wood borers, saws, scaling and chipping tools, air operated hoists etc.

Property:	Test Method:	Typical Values		
ISO Viscosity Grade	ISO 3448	46	100	150
Density @ 15°C kg/m ³	ASTM D4052 ,	0.88	0.89	0.9
Cst @ 40°C mm ² /s	ASTM D7042 ,	46	100	150
Viscosity Index	ASTM D2270	95	95	95
Flash Point deg C	ASTM D92 ,	220	238	246
Pour Point deg C	ASTM D97 ,	-12	-9	-9
Carbon Residue wt%	Ramsbottom,	0.63	0.64	0.66
P code		1685	1686	1687

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com. © Tesla Corporation, 2023

Product Nr: 1686	Date Issued: 01-11-2023	Date Superseded:	Revision nr: 2
------------------	-------------------------	------------------	----------------

TESLA Techno Products FZE

(Under License and Technology from Tesla Corporation, USA)

PO BOX 114132, Dubai, UAE

Phone +971 56 1144201/+971 50 6402887/+91 98201 87007 email:

info@teslalube.com; info@jaykamal.com; www.teslalube.com