



BETIA SS1110

Product Description: Tesla BETIA SS 1110 are high performance synthetic based motor cycle oil formulated from the latest additive technology and carefully selected base stocks. Tesla BETIA SS 1110 has been especially developed for all gasoline-, diesel-and LPG fuelled engines of motor cycle s.

Tesla BETIA SS 1110 has been designed to exceed the requirements of the Original Equipment Manufacturers' (OEM's) service fill specifications. Tesla Betia SS 1110 has very good thermo-oxidative stability, effectively preventing the formation of sludge and deposits, resulting in a prolonged engine life.

Tesla BETIA SS 1110 is recommended for all modern motor cycles , including high performance, turbo-charged, multi valve, direct injected gasoline-, diesel- and LPG fuelled engines..

Tesla BETIA SS 1110 exceeds the requirements of most modern European, North American and Japanese motor cycle manufacturers. Excellent ENGINE, CLUTCH and GEAR performance

Specifications: ACEA A3/B4, API SM/CF, Suitable for use : all kind of Motor cycles

Property:	Test Method:	Typical Values:		
SAE Viscosity Grade	SAE J300	15W-40	20W50	10W40
Density @ 15°C kg/m ³	ASTM D4052	883	883	879
Kinematic Viscosity @ 40°C mm ² /s	ASTM D7042	106	197	107
Kinematic Viscosity @ 100°C mm ² /s	ASTM D7042	15.3	21.2	14.5
Viscosity Index	ASTM D2270	>125	>120	>140
Flash Point (COC) °C	ASTM D92	215	>215	>210
Pour Point °C	ASTM D97	-24	-21	-30
P.Code		2699	2694	2700

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com © Tesla Corporation, 2011

Product Nr: 2699-1694-2700

Date Issued: 01-11-2011

Date Superseded:

Revision nr:

TESLA TECHNOPRODUCTS FZE

(A Subsidiary of York & Boston LLC USA)

Dubai Office: PO BOX 114132, Dubai, UAE

Phone: 971(4) 455 1070: Fax (971) (4) 455 1071 Cell: (971)(50) 1144201

email: info@teslalube.com