		TESLA CORPORATION BOX 114132, Dubai, I			
		ERIAL SAFETY DATA S			
		1 - PRODUCT IDENTIF			
SUPPLIER		E	MERGENCY TELEPH		
Tesla Corporation,			Company (+971)	561144201	
PO BOX 114132, Dubai, U/ CHEMICAL NAME AND SYNON		т	RADE NAME AND S		
Not applicable			POLARIS 1060, SAE 20W50		
CHEMICAL FAMILY			ORMULA		
Hydrocarbon			Not applicable		
		CHEMICAL AND PHY			
APPEARANCE	Clear bright yello		/iscosity, cst at 40°		
	Lube Oil odor		/iscosity, cst at 100		
RELATIVE DENSITY (Air=1) MELTING POINT, čC	>1 > 260		olubility in Water lash Point, Open Ci	NEGLIGIBLE	
VAPUK PRESSURE (IIIII Hg at			p. Gravity (H <sub>2</sub> U=1)	0.87 APPROX	
		ction III - INGREDIEN			
HAZARDOUS INGREDIENTS	Wt. Pct	TLV	ORAL	DERMAL	
	(Approx)		LD 50	LD 50	
Oil Mist (mineral)	< 85	5 mg/m² - 1			
Zinc Compounds	< 1.7	Unknown	Unknown	Unknown	
NON-HAZARDOUS INGREDIEN	-				
ADDITIVE AND/OR OTHER INGRED	-				
ingredients, their C.A.S numbers an listing of hazardous ingredients disc			-		
This material is an automotive/indu			-	=	
not designated as harmful to ozone.					
REGULATORY INFORMATION					
SARA Title III: This produt does not o	contain any chemcial subs	tance on the SARA Extremely	y Hazardous Substances Li	st. If this product contains any	
chemicals that are subject to the rep	porting requirements of S	ection 31 of Title III of the Su	perfund Amendments and	Re-authorization Act of 1986 and	
40 CFR Part 372, they will be listed i					
TSCA: This material is in compliance		s Control Act (15 USC 2601-2	2629) and all components	of this product appear on the	
Toxic Substance Control Act (TSCA) Clean Air Act: No ozone depleting cl		Stratospheric Ozone Protecti	on Section 602 of the Cla	an Air Act are present or used in the	
manufacturing process of this produ					
0,		RE AND EXPLOSION I	HAZARD DATA		
FLASH POINT, <sup>°</sup> C (Method)	215 COC	FLAMM	ABLE LIMITS: LEL	UEL	
			Un	known	
EXTINGUISHING MEDIA					
Foam, dry chemical, water		xide			
SPECIAL FIRE FIGHTING PROCEDURES Do not direct a solid stream of water into fire. Treat as a petroleum fire. Respiratory protection required for fire fighting personnel					
UNUSUAL FIRE AND EXPLOSIO		s a petroleum me. Respire	atory protection requir	ed for fire fighting personnel	
None					
	Section	n V - HEALTH HAZARI	D DATA		
THRESHOLD LIMIT VALUE (IF					
Not established. Oil Mist =	= 5 mg/m <sup>°</sup>				
EFFECTS OF OVEREXPOSURE					
Although there are no consistent pr					
and lung irritant. An existing skin, ex of carcinogens	e or lung irritation may b	e aggravated by direct conta	ict. No components are lis	ted on the USHA, IARC of NTP list	
or carcinogens	SECTION VI - EMI	RGENCY AND FIRST	AID PROCEDURES		
EYE CONTACT					
Flush immeidately with water until i SKIN CONTACT	rritation subsides				
Wash affected skin area with mild so INGESTION	pap and water				
Do not induce vomitting. Contact a INHALATION	Physician				
Remove to fresh air. If not breathing	g, give artificial respiration	n. Contact a physician			
POLARIS 1060, SAE 20W50					
Effective Date 1-Dec-11	Print Date:	3/19/2014 TESLA CORPORATION	J	Page 1 of 2	

PO BOX 114132, Dubai, UAE

### TRADE NAME AND SYNONYMS

STABILITY (Thermal, Light, Etc.)

### MATERIAL SAFETY DATA SHEET POLARIS 1060, SAE 20W50 SECTION VII - REACTIVITY DATA CONDITIONS TO AVOID

Contact with nuclear radiation and strong oxidising agents

Stable INCOMPATIBILITY (Materials to avoid)

Strong oxidizing materials

HAZARDOUS DECOMPOSITION PRODUCTS

Dense smoke, oxides of C, S, Mg, Ca, N, P, Zn and B. hydrogen sulfide

HAZARDOUS POLYMERIZATION

Will not occur

## SECTION VIII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition. Treat as a petroleum oil spill WASTE DISPOSAL METHOD

Incinerate where permitted under federal, state and local laws. Used petroleum products may be recycled through re-refining process EYE PROTECTION

Sufficient to avoid direct contact

SKIN PROTECTION

Protective neoprene or plastic gloves may be desired

**RESPIRATORY PROTECTION** 

Usually not needed in o pen, unconfined areas

VENTILATION

Usually not needed in open, unconfined areas

OTHER

Usualy not needed

#### SECTION IX SPECIAL PRECUATIONS

Close containers when not in use. Keep away from heat, sparks, open flames, and strong oxidants. Avoid eye contact and prolonged skin contat. Avoid breathing oil mists. Wash thoroughly after handling

# SECTION X HAZARD RATINGS

There are several recognised and acceptes systems that assign hazard ratings to materials. Although this product has not been evaluated specifically against these systems, the ratings for the National Fire Protection Association (NFPS) and the National Paint and Coating Association's Hazardous Material Identification Systems (HMIS) are:

	NFPA	HMIS
Health	2	1
flammability	1	1
Reactivity	1	1

POLARIS 1060, SAE 20W50 Effective Date 1-Dec-11