



POLARIS 1060

Product Description: **Polaris 1060** is mineral passenger car motor oil formulated from carefully selected additives and mineral base stocks. Polaris 1060 has been developed for older gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

Polaris 1060 has good thermo-oxidative stability, effectively preventing the formation of sludge and deposits. Effective rust inhibitors prevent corrosion of critical engine parts. The use of advanced anti-wear additives results in prolonged engine life. Good 'stay in grade' properties of the oil ensure reliable lubrication even at higher load- and temperature conditions.

Polaris 1060 is recommended for older vehicles, including turbo-charged gasoline-, diesel- and LPG fuelled engines of passenger cars and light commercial vehicles.

Specifications: API SF/CD, CCMC G2/PD-1, U.S. Military 2104B, MIL-L-46152C and SAE 15W40, SAE 40 or 20W50

Property:	Test Method:	Typical Values:		
SAE Viscosity Grade	SAE J300	15W-40	20W50	40
Density @ 15°C kg/m ³	ASTM D4052	883	889	885
Kinematic Viscosity @ 40°C mm ² /s	ASTM D7042	109	192	100
Kinematic Viscosity @ 100°C mm ² /s	ASTM D7042	15.3	21.2	15.6
Viscosity Index	ASTM D2270	>125	>130	95
Flash Point (COC)°C	ASTM D92	235	238	215
Pour Point °C	ASTM D97	-17	-15	-9
Total Base Number (TBN) mgKOH/g	ASTM D2896	4.9	4.9	4.9
P.Code		1001	1002	1003

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com. © Tesla Corporation, 2023

Product Nr: 1001/1002

Date Issued: 01-11-2023

Date Superseded:

Revision nr: 2

TESLA Techno Products FZE

(Under License and Technology from Tesla Corporation, USA)

PO BOX 114132, Dubai, UAE

Phone +971 56 1144201/+971 50 6402887/+91 98201 87007 email:

info@teslalube.com; info@jaykamal.com; www.teslalube.com